





SR Series Metal Alloy Shunt Two Terminal Low-Resistance Resistor Product Specifications

Document No.	S-10-12-04-17
Released Date	2025/07/22
Page No.	1/8


■ Metal Alloy Shunt Two Terminal Low-Resistance Chip Resistor— SR Series



SR2527



SR5930/3920



SR2512



SR1206

■ Application

- Power modules
- High current Power Supply
- Motor Driver
- Industrial
- Battery management system
- Automotive

■ Features

- Low Resistance / TCR
- Excellent long-term stability
- RoHs compliant and halogen free
- Lead free
- High precision current sensing and voltage division
- Excellent Anti-Surge ability
- AEC-Q200 compliant
- Low Inductance $\leq 3\text{nH}$ for Materials:
S (MnCuSn) / M(MnCu) / R (NiCrAl) / C (Cu)

■ Parts Number Explanation

■ Example:

SR	2512	20	F	R004	M	Z
Product Type	Size (Inch)	Rated Power	Tolerance	Resistance	Material	Optional
	1206 2512 2527 3920 5930	20=2.00W 25=2.50W 30=3.00W 50=5.00W .. T0=10.0W T2=12.0W	F : $\pm 1\%$ G : $\pm 2\%$ J : $\pm 5\%$	0m10=0.1mR 0m50=0.5mR R001=1.0mR R005=5mR R000=Jumper	S : MnCuSn M : MnCu F : FeCrAl R : NiCrAl C : Cu	



SR Series Metal Alloy Shunt Two Terminal Low-Resistance Resistor Product Specifications

Document No. S-10-12-04-17

Released Date 2025/07/22

Page No. 2/8

■ Standard Electrical Specifications

Type	Power Rating at 70℃	T.C.R. (ppm/℃)	Max. Rating Current(A)	Max. Overload Current(A)	Resistance Range (mΩ)	Material	Operating Temperature Range (℃)
					1.0% (F) 、 2.0% (G) 、 5.0% (J)		
SR1206	2W	≤±300	81.6	182.57	0.3	MnCuSn	- 65 ~ + 170
	2W	≤±200	63.24	141.42	0.5	MnCuSn	
	2W	≤±150	44.72	100	1	MnCu	
SR2512	9W	125±50	212	-	0.2	MnCuSn	
	6W	≤±200	154.92	346.41	0.25	MnCuSn	
	6W	≤±150	141.42	316.22	0.3	MnCuSn	
	6W	≤±115	109.54	244.94	0.5	MnCu	
	5W	≤±115	81.65	182.57	0.75	MnCu	
	5W	≤±100	70.71	158.11	1	MnCu	
	5W	≤±50	50	111.80	2	NiCrAl	
	4W	≤±50	36.51	81.65	3	NiCrAl	
	4W	≤±50	31.62	70.71	4	NiCrAl	
	3W	≤±50	27.38	61.23	4	NiCrAl	
	2.5W	≤±50	22.36	50	5	FeCrAl	
SR2527	8W	≤±200	282	-	0.1	MnCuSn	
			200	-	0.2	MnCuSn	
SR3920	5W	-	160	-	0 (≤ 0.2 mΩ)	Cu	
	12W	≤±200	244.94	547.72	0.2	MnCuSn	
	10W	≤±150	182.57	408.24	0.3	MnCu	
	9W	≤±75	134.16	300	0.5	MnCu	
	8W	≤±50	89.44	200	1	FeCrAl	
	7W	≤±50	83.66	187.08	1	MnCu	
	7W	≤±50	68.31	152.75	1.5	FeCrAl	
	6W	≤±50	54.77	122.47	2	FeCrAl	
	5W	≤±50	40.82	91.28	3	NiCrAl	
	4W	≤±50	31.62	70.71	4	FeCrAl	
	3W	≤±50	24.49	54.77	5	FeCrAl	
SR5930	15W	≤±220	387.29	866.02	0.1	MnCuSn	
	15W	≤±100	273.86	612.37	0.2	MnCu	
	10W	≤±100	182.57	408.24	0.3	MnCu	
	8W	≤±75	126.49	282.84	0.5	MnCu	
	8W	≤±50	89.44	200	1	FeCrAl	
	7W	≤±50	59.16	132.28	2	FeCrAl	
	5W	≤±50	40.82	91.28	3	FeCrAl	

● Power rating is guaranteed when terminal temperature of resistor is below 70℃




SR Series Metal Alloy Shunt Two Terminal Low-Resistance Resistor Product Specifications

Document No. S-10-12-04-17

Released Date 2025/07/22

Page No. 3/8

■ Type Dimension



■ Dimension

Unit : mm

Type	Resistance	L	W	H	T	A	C (Max.)	p	Material
SR1206	0.3mR	3.2±0.3	1.65±0.3	1.20±0.15	0.90±0.15	0.80±0.2	0.3	0.30±0.1	MnCuSn
	0.5mR	3.2±0.3	1.65±0.3	0.90±0.15	0.60±0.15	0.80±0.2	0.3		MnCuSn
	1mR			0.90±0.15	0.40±0.15			0.50±0.1	MnCu
SR2512	0.2mR	6.5±0.3	3.25±0.3	1.50±0.15	1.00±0.15	2.1±0.2	1.0	0.50±0.15	MnCuSn
	0.25mR			1.35±0.15	1.00±0.15	0.90±0.2	0.4	0.35±0.1	MnCuSn
	0.3mR			1.17±0.15	0.82±0.15				MnCuSn
	0.5mR			1.07±0.15	0.72±0.15				MnCu
	0.75mR			0.95±0.15	0.6±0.15				MnCu
	1mR			0.73±0.15	0.38±0.15				MnCu
	2mR			0.96±0.15	0.61±0.15				NiCrAl
	3mR			0.76±0.15	0.41±0.15				NiCrAl
	4mR			0.70±0.15	0.35±0.15				NiCrAl
	5mR			0.66±0.15	0.31±0.15				FeCrAl
SR2527	0.1mR	6.5±0.2	6.85±0.2	1.50±0.15	1.00±0.15	2.1±0.2	1.0	0.50±0.15	MnCuSn
	0.2mR			1.00±0.20	0.60±0.15			0.40±0.15	MnCuSn
SR3920	0.2mR	10.2±0.30	5.20±0.3	1.98±0.15	1.48±0.15	1.8±0.3	0.6	0.50±0.1	MnCuSn
	0.3mR			1.92±0.15	1.42±0.15				MnCu
	0.5mR			1.36±0.15	0.86±0.15				MnCu
	0mR/1mR			0.92±0.15	0.42±0.15				Cu/MnCu
	1mR			1.87±0.15	1.37±0.15				FeCrAl
	1.5mR			1.46±0.15	0.96±0.15				FeCrAl
	2mR			1.19±0.15	0.69±0.15				FeCrAl
	3mR			0.94±0.15	0.44±0.15				NiCrAl
	4mR			0.85±0.15	0.35±0.15				FeCrAl
	5mR			0.85±0.15	0.35±0.15				FeCrAl



SR Series Metal Alloy Shunt Two Terminal Low-Resistance Resistor Product Specifications

Document No.	S-10-12-04-17
Released Date	2025/07/22
Page No.	4/8

Dimension

Unit : mm


Type	Resistance	L	W	H	T	A	C (Max.)	p	Material
SR5930	0.1mR	15±0.3	7.75±0.3	1.92±0.15	1.42±0.15	4.2±0.2	1.0	0.50±0.1	MnCuSn
	0.2mR			1.92±0.15	1.42±0.15				MnCu
	0.3mR			1.44±0.15	0.94±0.15				MnCu
	0.5mR			1.08±0.15	0.58±0.15				MnCu
	1mR			1.37±0.15	0.87±0.15				FeCrAl
	2mR			0.95±0.15	0.46±0.15				FeCrAl
	3mR			0.90±0.15	0.40±0.15				FeCrAl

Performance Characteristics

Power Derating Curve

The Operating Temperature Range: -65°C ~+170°C.

Terminal temperatures above 70°C, power rating must be derated in accordance with the curve as below :



Rating Current

The following equation may be used to determine the DC (Direct Current) or AC (Alternating Current) (RMS, root mean square value) of normal rated power. However, if the result value exceeds the highest current of regulated standards, the highest normal rated power is to be used

$$I = \sqrt{P/R}$$

I = Rating current (A)
P= Rating Power (W)
R= Resistance(Ω)

Marking Format:

- 1206 2527 and 2512 0.2mΩ no marking.
- 2512/3920/5930 marking are 3 digits. 3920 0mΩ is no marking.
- “L” designates the decimal location in milliohm
e.g. 3mΩ the product marking is 3L0.
0.3mΩ the product marking is L30.
- The criteria to distinguishing the mark on the surface of products are that characters can be identified.



SR Series Metal Alloy Shunt Two Terminal Low-Resistance Resistor Product Specifications

Document No. S-10-12-04-17
Released Date 2025/07/22
Page No. 5/8

Reliability Test and Requirement

Test Item	Test Method	Procedure	Requirements
Temperature Coefficient of Resistance (T.C.R)	JIS-C-5201-1 4.8 IEC-60115-1 4.8	At 25°C /+125°C, 25°C is the reference temperature	As Spec
Short Time Overload	JIS-C-5201-1 4.13 IEC-60115-1 4.13	The number of rated power are as follows: - SR1206: 5 times of rated power - SR2512: 5 times of rated power (not included 0.2mΩ) - SR3920: 5 times of rated power SR3920 Jumper(0mΩ): 160A - SR5930: 5 times of rated power for 5 seconds.	$\Delta R/R1 \leq \pm(1.0\%+0.0005\Omega)$ Jumper : $\leq 0.2mR$
High Temperature Exposure (Storage)	MIL-STD-202 Method 108	1000 hrs. @ T=170°C. Unpowered. Measurement at 24±4 hours after test conclusion.	$\Delta R/R1 \leq \pm(1.0\%+0.0005\Omega)$ Jumper : $\leq 0.2mR$
Temperature Cycling	JESD22 Method JA-104	1000 Cycles (-55°C to +155°C) Measurement at 24±4 hours after test conclusion. 30min maximum dwell time at each temperature extreme.	$\Delta R/R1 \leq \pm(1.0\%+0.0005\Omega)$ Jumper : $\leq 0.2mR$
Biased Humidity	MIL-STD-202 Method 103	1,000 hours; 85°C / 85% RH, 10% of operating power. Measurement at 24±4 hours after test conclusion.	$\Delta R/R1 \leq \pm(1.0\%+0.0005\Omega)$ Jumper : $\leq 0.2mR$
Operation Life	MIL-STD-202 Method 108	Condition D Steady State TA=125°C at derated power. Measurement at 24±4 hours after test conclusion.	$\Delta R/R1 \leq \pm(1.0\%+0.0005\Omega)$ Jumper : $\leq 0.2mR$
Moisture Resistance	MIL-STD-202, Method 106	Humidity of 90~98% and a temperature of 25°C / 65°C ,10 cycles	$\Delta R/R1 \leq \pm(1.0\%+0.0005\Omega)$ Jumper : $\leq 0.2mR$
Mechanical Shock	MIL-STD-202 Method 213	Test ½ Sine Pulse, Peak value: 100g, normal duration: 6ms, Velocity change:12.3ft/sec.	$\Delta R/R1 \leq \pm(0.5\%+0.0005\Omega)$ Jumper : $\leq 0.2mR$
Vibration	MIL-STD-202 Method 204	5 g's for 20 min., 12 cycles each of 3 orientations. Note: Test from 10-2000Hz	$\Delta R/R1 \leq \pm(0.5\%+0.0005\Omega)$
Board Flex	AEC Q200-005	Beading once for 60 seconds ,2mm	$\Delta R/R1 \leq \pm(1.0\%+0.0005\Omega)$ Jumper : $\leq 0.2mR$
Solderability	J-STD-002	245±5°C 3 sec.	>95% coverage(electrode area)

● Note : All Reliability test should follow De-rating curve , terminal temperature of component should be below 70°C .

● Note : Footprint size, solder insufficient, excessive solder, solder void and component shifted will affect the resistance accuracy after IR reflow. Circuit calibration is a must to be done by functional test.




SR Series Metal Alloy Shunt Two Terminal Low-Resistance Resistor Product Specifications


Document No.	S-10-12-04-17
Released Date	2025/07/22
Page No.	6/8

■ Anti-Surge Ability:


Pulse Power Characteristics – SR1206 0.5mR




SR2512 Series
Pulsed Power Characteristics



SR 3920 Series
Pulsed Power Characteristics



SR 5930 Series
Pulsed Power Characteristics





SR Series Metal Alloy Shunt Two Terminal Low-Resistance Resistor Product Specifications


Document No. S-10-12-04-17

Released Date 2025/07/22

Page No. 7/8


Recommended Customer Soldering Parameters:

Solder reflow Temperature condition



- The peak temperature of soldering heat is 260 for 10s

Recommend Land Pattern Design



Dimension

Unit: mm

Type	Resistance Range	a	b	i
SR1206	0.3mΩ~1mΩ	2.10	1.80	1.40
SR2512	0.25mΩ~5mΩ	1.80	3.40	3.80
SR2512	0.2mΩ	2.8	3.5	2.1
SR2527	0.1mΩ and 0.2mΩ	2.8	7.1	2.1
SR3920	0mΩ, 0.2mΩ~5mΩ	2.70	6.20	5.60
SR5930	0.1mΩ~3mΩ	5.20	8.75	5.60

Packing Quantity

Type	PCS / Reel
SR1206	2,000
SR2512	4,000
SR2512 0.2mΩ	3,000
SR2527	2,000
SR3920	3,000
SR5930	2,000

Storage Temperature

Temperature : 25±5°C , Humidity : 60±20%



SR Series Metal Alloy Shunt Two Terminal Low-Resistance Resistor Product Specifications

Document No. S-10-12-04-17


Released Date 2025/07/22

Page No. 8/8

■ Appendix For SMD Chip Resistor

● Packaging Information

■ Reel Dimensions




■ Dimension

Unit: mm

Reel Type / Tape	A	ΦB	ΦC	ΦD	W	ΦM
7" reel for 8 mm embossed	2±0.5	13.0±0.5	17.7±0.5	60.0±0.5	12.0±0.5	178±1.0
10" reel for 12 mm embossed	2±0.5	13.0±0.5	17.7±0.5	62.0±0.5	16.5±0.5	250±1.0
13" reel for 12 mm embossed	2.3±0.5	13.5±0.5	17.7±0.5	99.0±0.5	16.7±0.5	330±1.0
13" reel for 16 mm embossed	2.5±0.5	13.5±0.5	17.7±0.5	99.0±0.5	20.7±0.5	330±1.0
13" reel for 24 mm embossed	2.5±0.5	13.5±0.5	17.7±0.5	99.0±0.5	29.4±0.5	330±1.0

■ Embossed Dimensions



■ Dimension

Unit: mm

Item	Resistance (Ω)	W	P	E	F	ΦD	G	H	A	B	T1
SR1206	0.3m, 0.5m, 1m	8.0±0.30	4.0±0.10	1.75±0.10	3.5±0.10	1.50 ^{+0.1} ₋₀	4.0±0.10	2.0±0.10	1.88±0.10	3.56±0.10	1.40±0.10
SR2512	0.2m	12.0±0.30	8.0±0.10	1.75±0.10	5.5±0.10	1.50 ^{+0.1} ₋₀	4.0±0.10	2.0±0.10	3.60±0.10	6.80±0.10	2.00±0.10
	0.25m, 0.3m, 0.5m, 0.75m, 2m	12.0±0.30	4.0±0.10	1.75±0.10	5.5±0.10	1.50 ^{+0.1} ₋₀	4.0±0.10	2.0±0.10	3.55±0.10	6.75±0.10	1.40±0.10
	1m, 3m	12.0±0.30	4.0±0.10	1.75±0.10	5.5±0.10	1.50 ^{+0.1} ₋₀	4.0±0.10	2.0±0.10	3.55±0.10	6.75±0.10	1.10±0.10
	4m, 5m	12.0±0.30	4.0±0.10	1.75±0.10	5.5±0.10	1.50 ^{+0.1} ₋₀	4.0±0.10	2.0±0.10	3.55±0.10	6.75±0.10	0.80±0.10
SR2527	0.1m, 0.2m	16.0±0.30	12.0±0.10	1.75±0.10	7.5±0.10	1.50 ^{+0.1} ₋₀	4.0±0.10	2.0±0.10	7.25±0.10	6.9±0.10	1.90±0.10
SR3920	0.2m, 0.3m, 0.5m, 2m, 1mR(8W), 1.5mR	16.0±0.30	8.0±0.10	1.75±0.10	7.5±0.10	1.50 ^{+0.1} ₋₀	4.0±0.10	2.0±0.10	5.5±0.10	10.8±0.10	1.97±0.10
	Jumper(0m), 1m(7W), 3m, 4m, 5m	16.0±0.30	8.0±0.10	1.75±0.10	7.5±0.10	1.50 ^{+0.1} ₋₀	4.0±0.10	2.0±0.10	5.5±0.10	10.8±0.10	1.25±0.10
SR5930	0.1m, 0.2m, 0.3m, 1m	24.0±0.30	12.0±0.10	1.75±0.10	11.5±0.10	1.50 ^{+0.1} ₋₀	4.0±0.10	2.0±0.10	8.3±0.10	15.4±0.10	2.30±0.10
	0.5m, 2m, 3m	24.0±0.30	12.0±0.10	1.75±0.10	11.5±0.10	1.50 ^{+0.1} ₋₀	4.0±0.10	2.0±0.10	8.3±0.10	15.4±0.10	1.40±0.10